

BRUSH CUTTER

EXTREME DUTY SERIES 2 CLOSED/OPEN FRONT



The Blue Diamond® Extreme Duty Series 2 Closed and Open Front Brush Cutters are aggressive - even the standard-flow models outperform most high-flow cutters. The durable push bar keeps trees off the deck. The very heavy duty direct-drive system makes this commercial-grade cutter extremely reliable.



OPEN-FRONT



CLOSED-FRONT

60" STANDARD FLOW:

- 3 double-sided blades
- 3/4" thick blade carrier
- 4000 Series geroler motor
- 5" diameter cutting capacity
- 15 – 22 GPM flow range
- Dual-direction cutting

60" HIGH FLOW:

- 3 double-sided blades
- 3/4" thick blade carrier
- 6000 Series geroler motor
- 5" diameter cutting capacity
- 27 – 40 GPM flow range
- Dual-direction cutting

72" STANDARD FLOW:

- 4 double-sided blades
- 3/4" thick blade carrier
- 4000 Series geroler motor
- 6" diameter cutting capacity
- 13 – 26 GPM flow range
- Dual-direction cutting

72" HIGH FLOW:

- 4 double-sided blades
- 3/4" thick blade carrier
- 6000 Series geroler motor
- 8" diameter cutting capacity
- 27 – 45 GPM flow range
- Dual-direction cutting

PART NUMBER	MODEL	REQUIRED FLOW	WEIGHT
103015-2	60" Standard Flow-Closed Front	15-22 GPM	1,235 lbs
103020-2	72" Standard Flow-Closed Front	16-26 GPM	1,617 lbs
103016-2	60" Standard Flow-Open Front	15-22 GPM	1,220 lbs
103027-2	72" Standard Flow-Open Front	13-18 GPM	1,794 lbs
103025-2	72" Standard Flow-Open Front	16-26 GPM	1,794 lbs
103017-2	60" High Flow-Open Front	23-40 GPM	1,225 lbs
103023-2	72" High Flow-Closed Front	27-35 GPM	1,617 lbs
103024-2	72" High Flow-Closed Front	36-45 GPM	1,617 lbs
103030-2	72" High Flow-Open Front	27-35 GPM	1,794 lbs
103032-2	72" High Flow-Open Front	36-45 GPM	1,794 lbs

888-376-7027

info@bluediamondattachments.com

BlueDiamondAttachments.com

888-377-7027

4512 Anderson Rd., Knoxville, TN 37918

Monday - Friday, 8am - 5pm EST

