

# POWER RAKE EXTREME DUTY



When productivity matters...look no further. Travel faster, cut deeper and get on to the next job! With skid steer machine sizes increasing in the industry, there is a need for more powerful and durable power rake/spoil conditioner attachment. The Blue Diamond® Power Rake - Extreme Duty is designed to power through jobs where other fail, and is set up for simple servicing. This low speed, high torque Geroler hydraulic motor and optimal drum size product maximum torque, and the motor is kept out of the way, maximizing usable width in tighter areas. Aggressive 2" teeth are ideal for leaving a fresh seed bed with fewer passes.



PART NUMBER	MODEL	WEIGHT
132126	48" Power Rake, Replaceable Teeth (W/Skid Steer Mount)	590 lbs
132110	72" Power Rake, Replaceable Teeth	1,136 lbs
132115	84" Power Rake, Replaceable Teeth	1,160 lbs
132120	96" Power Rake, Replaceable Teeth	1,185 lbs
132125	48" Power Rake, Fixed Teeth (W/Skid Steer Mount)	590 lbs
132112	72" Power Rake, Fixed Teeth	1,085 lbs
132117	84" Power Rake, Fixed Teeth	1,110 lbs
132122	96" Power Rake, Fixed Teeth	1,135 lbs
332520	Hydraulic Angle Kit, Fits 72-84" (Universal harness included, OEM connection sold separately)	51 lbs
332525	Hydraulic Angle Kit, Fits 96" (Universal harness included, OEM connection sold separately)	52 lbs
132065	Power Rake Manual Angle Kit, Fits 72-96"	20 lbs
132066	Power Rake Manual Angle Kit, Fits 120"	25 lbs
132050	Optional Power Rake Skid Shoes	30 lbs
216900	OEM 14-Pin Harness (Specify Machine)	1 lbs
*216915	OEM 14-Pin JD Harness	3 lbs
*216905	OEM 8-Pin Cat Harness	3 lbs
*216950	OEM 7-Pin Bobcat Harness	1 lbs
200011	OEM Extension Harness	1 lbs

## FEATURES INCLUDE

- Low speed, high torque Geroler hydraulic motor
- 4" x 4" square tube frame
- 18-26 GPM hydraulic flow, max 4000 PSI
- Optional replaceable teeth vs fixed teeth
- 1" front wheel axis vs competitive 3/4"
- 1.5" motor shaft and high pressure seals
- 5 position, 20 degree angle, manual or hydraulic
- 6 3/4" drum diameter, 10 3/4" including teeth
- Double struts on the castors



Side Plate with Skid Shoe



Airless tires - NO flats

*Includes mount, high torque, optional replaceable teeth, requires hoses or hydraulic angle kit (sold separately), larger model, protected bearings. Optional harden steel or carbide teeth that are either replaceable or fixed. \*Requires PN 200011*

888-376-7027

info@bluediamondattachments.com

BlueDiamondAttachments.com

888-377-7027

4512 Anderson Rd., Knoxville, TN 37918

Monday - Friday, 8am - 5pm EST

Revised: 01.29.25

